

## HIGH DENSITY LEDs

With both 45W and 80W LED variants available, light output is maximised through use of the latest, most advanced and efficient LED technology available.



## OVER VOLTAGE PROTECTION

In-built into the electronic circuitry to prevent damage, alongside protection against reverse polarity.

## 5,000 KELVIN COLOUR TEMPERATURE FOR MAXIMUM DEFINITION

While reducing fatigue and eye strain that can come from using higher colour ranges.

## MALE & FEMALE DEUTSCH CONNECTORS INCLUDED

Part no. DT06-2S / DT04-2P.

# LAZER

HIGH PERFORMANCE LIGHTING

# UTILITY SERIES

# HEAVY DUTY LED WORK LAMP



## EMC PROTECTION

Approved to CISPR-25 Class 3 ensures no interference with other electrical machinery or appliances.

## VACUUM-METALLISED REFLECTOR TECHNOLOGY

Designed and engineered in the UK to deliver light further and wider, in a symmetrical flood beam pattern.



**UTILITY-45**  
45W  
4560 LUMENS

**UTILITY-80**  
80W  
8820 LUMENS

## CAE OPTIMISED 'MATRIX' COOLING SYSTEM

Provides more efficient thermal management to maximise light output.

## WIDE MOUNTING OPTION & SLIMLINE MOUNTING OPTION

Both provide 360° rotation, and 120° angle up / down, from a horizontal or vertical mounting position.

## AUTOMOTIVE GRADE CORROSION RESISTANCE

E-coat pre-treatment prior to black powder coating ensures exceptional corrosion resistance including against harsh chemical treatments.

## ELECTRONIC THERMAL MANAGEMENT

Optimises light output considering the environmental and thermal conditions of the lamp.

## 'UNBREAKABLE' POLYCARBONATE LENS

3mm lexan polycarbonate with hardcoat lacquer provides exceptional protection from impact and heat.

